AFRL-SN-HS-TR- 2002-040

NON-LINEAR OPTICAL SIGNAL PROCESSING

Mark Cronin-Golomb
Jed Khoury

Tufts University
Electro-Optics Technology Center
Medford MA 02155

FINAL REPORT: AUGUST 1994 – AUGUST 1995

APPROVED FOR PUBLIC RELEASE – DISTRIBUTION UNLIMITED



AIR FORCE RESEARCH LABORATORY
Sensors Directorate
80 Scott Dr
Hanscom AFB MA 01731-2909

TECHNICAL REPORT

Title: Non Linear Optical Signal Processing

PUBLICATION REVIEW

This report has been reviewed and is approved for publication:

APPROVED:

CHARLES WOODS
AFRL/SNHC
Optoelectronic Technology Branch
Electromagnetics Technology Division

APPROVED:

ROBERT V. McGAHAN
Technical Advisor
Electromagnetics Technology Division

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1. AGENCY USE ONLY *(Leave blank)*	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED
	1 September 1995	FINAL 31 August 1994 - 30 August 1995

4. TITLE AND SUBTITLE
Non Linear Optical Signal Processing

5. FUNDING NUMBERS
C-F30602-94-C-0262
PE - 61102F
PR - E-4-7410
PROJ - 2305
TA - D7
WU - P3

6. AUTHOR(S)
Jehad Khoury, Mark Cronin-Golomb

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)
Tufts University
Electro-Optics Technology Center
Medford, MA 02155

8. PERFORMING ORGANIZATION REPORT NUMBER

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)
Charles Woods
AFRL/SNHC
80 Scott Drive
Hanscom AFB, MA 01731-2909

10. SPONSORING/MONITORING AGENCY REPORT NUMBER
AFRL-SN-HS-2002-040

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION AVAILABILITY STATEMENT
Approved for public release; distribution unlimited.

12b. DISTRIBUTION CODE
a

13. ABSTRACT *(Maximum 200 words)*

In this work we presented a two port nonlinear joint transform correlator with two complimentary results. This correlator is based on a two port photorefractive limiting quadratic processor. In the limiting regime we demonstrated experimentally and by computer simulation, that the correlation operation is like a phase extraction correlator operation, regardless of the sign of the coupling coefficient. However, for positive coupling coefficients and intermediate beam ratios, one port performs as a phase-only filter and the other as a classical matched filter.

14. SUBJECT TERMS	15. NUMBER OF PAGES
nonlinear image	4
	16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	SAR

Nonlinear Optical Image Processing

September 1, 1995

Nonlinear joint transform correlator

In this work we presented two port nonlinear joint transform corrlator with two complementary results. This correlator is based on using a two port photorefractive limiting quadratic processor. In the limiting regime we demonstrated experimentally and by computer simulation, that the correlation operation is like a phase extraction correlator operation, regardless of the sign of the coupling coefficient . However, for positive coupling coefficients and intermediate beam ratios, one port performs as a phase-only filter and the other as a classical matched filter.

Related references

i) "Analysis of dual discrimination ability of two-port photorefractive joint-transform correlator," To appear in Applied Optics.

Optimal correlation design for associative memory

Most of the implementations of associative memories are based on using the Hopfield algorithm. The basis of all holographic implementations uses holograms which multiplex several holographic matched filters. It is well-known that the classical matched filter has a poor discrimination ability and therefore most of the implementation based on the Hopfield algorithm has poor performance. To improve the performance, we first derived the optimal algorithm which maximizes the criteria peak-to noise-ratio (or the discrimination ability). Our algorithm is basically a modification of the Yaroslavsky algorithm.

The hardware implementation of this algorithm is not easy. Therefore, we suggest several

alterations which approximate the optimal algorithm. One alteration is based on using nonlinear saturation amplifiers in architectures with holograms which multiplex several matched filters. The use of a saturation amplifier has proven its effectiveness by ōthers in recalling all of the information when the memory is addressed with 1/50 of the full information. These experimental results verify our derivation of the new algorithm and it's modification.

Related references

"Nearly optimal correlation design for shift associative memories," Appl. Opt. 34, 3971-3980 (1995)

Homodyne and Heterodyne Frequency Classifier

In this work, we demonstrated the operation of an externally- pumped phase conjugate mirror as a frequency division demultiplexer. In this architecture, a self-pumped phase conjugator is pumped by two beams. One is a reference beam, which is phase conjugated via a self-pumped mechanism, and the other is a signal beam, which is conjugated via pumping by the conjugate of the reference beam. For the demultiplexing operation, the signal beam multiplexes many spatial-temporal signals, while the reference beam is temporally modulated. Demultiplexing occurs only if the frequency of the modulation in the reference beam is equal to the frequency of one of the signals.

Related References

"Demultiplexing and phase-locking via self pumped phase conjugate mirror" The Proc. of the SPIE, B. Javidi and J. L. Horner edited, 2565, 155-256 (1995)